

Annex A Specifications offer for RFQ BKA_25_04

ITEM	Specification	LRC DRR Specifications	Qty	unit price excluded VAT	Total price excluded VAT
<p>Wheel Fire Extinguisher 50 ltr</p>	<p>Supply 50 Ltr Wheeled Foam fire Extinguisher, Foam AFFF 6% AB, F50BEMED, Cylinder material is DD11 EN10111, Approved to EN1866, High Quality 3%.Foam, Long throw foam nozzle with grip control, One person operation and movement with Refillable stored pressure unit. Working Pressure to be not less then 12 Bar, Test Pressure not less then 22 Bar, Temperature Range (- 5/+60), 2 Year Warranty and testing check list of the Extinguishers to be provided, dimensions should be 890x310 mm, Sample or catalog should be provided for checking.</p>	<p>Fire ext powder 30 kg: Certification: UL Listed Standards: ANSI / UL 299, ANSI / UL 711 Fire rating: Class A, B and C fire Temperature: - 40°C to 49°C Pressure: 195 psi Chemical Agent: ABC powder, ammonium phosphate-based chemicals Hose: Rubber Cylinder: Deep-drawn steel Cylinder valve: Aluminum, with pressure gauge and SS handle Wall hook or wall bracket should be included</p>	<p>7</p>		
<p>Metal box (basket)</p>	<p>Supply metal basket with dimensions 1.5 m length, 1.8 m height, and 70 cm width. It should be made of RHs 30x30x1 mm, should be welded vertically with 15 cm in between and horizontally with 30 cm in between, the basket should be leveled with 10 cm, the floor of the basket is mesh of crossed RHs 30x30x1 mm, with 10 cm distance in between, also a same specification for the cover and it should be able to open with good quality joints and lock with 6 copies of keys, all box members should be painted 2 layers of anti-rust paint and 2 layers of oil paint with color should be approved by IOM. The supplier should provide a sample before supplying.</p>	<p>Color: Flame Red- Powder coated Material: 0.9 Zinc Anneal Sheet Metal Lock: Cam Lock or emergency Break Glass With Glass Window Dimension: 710 x 320 x 220 (estimated)</p>	<p>7</p>		
<p>Fire Extinguisher blanket</p>	<p>Supply Fire-Fighting blanket size (4FT*4FT) made by smooth continuous filament glass fiber. Size: 4ft x 4ft (1.2m x 1.2m) Material: Smooth continuous filament glass fiber</p>	<p>Glass fiber fabric independently tested and certified to BS 476 parts 4 and 7 Blanket made from woven glass fiber fabric (totally asbestos-free) Containers can be wall-mounted Easy and quick withdrawal of blanket from container English and/or other language instruction labels available, Clear pictorial instructions.</p>	<p>7</p>		

<p>Fire-Fighting helmet</p>	<p>Supply Fire-Fighting helmet, yellow color and good quality</p>	<p>outer shell material: High temperature polyetherimide(PEI) plastic with single reinforcement at tope; Face shield material:polyetherimide (PEI) plastic Face shield material:polyetherimide (PEI) plastic Head Shell Heat resistant: 260°C All-round head protection.Free adjustment of the helmet.Adjustable suspension systemChin strapHigh temperature, heat resistant, anti-impact, anti abrasion, shock absorption and fire proof.Color:yellow/red</p>	<p>7</p>		
<p>Safety Boot Heavy Duty (CAT)</p>	<p>Supply safety shoes Caterpillar (CAT) or equivalent Footwear Men</p>	<p>Outer sole:made in one-piece slip-resistant rubber Outer materail:PMIA three-in-one aramid fabric Inner lining fabric:flame retardant treatment. Thermal barrier:aramid fiber felt Midsole: steel Toecap: steel In the front of the barrel, it has a tibia protection in yellow,made of rubber Size :38-48 have resistance to: abrasion, perforation and heat penetration, has additional reinforcements on the instep and sides</p>	<p>7</p>		
<p>Fire safety glasses</p>		<p>Made of asbestos,can protect the fire, widely used in fire-fighting,oil,coal, and mining industries ect. Specification: 1)good tensile strength and good stays and anticorrosive,performance flameretardant, prevent water resistance, resistance to grind, wet through every hot, prevent static electricity, comfortable. 2)Length > 30 cm 3)Thickness 2.0mm</p>	<p>7</p>		

<p>Fire safety gloves</p>		<p>The gloves have four layer made of aramid outer layer: adopts the high strength fabric with flame retardant anti - acid and alkali, anti - oil, anti - static, etc.. Waterproof layer: waterproof and moisture permeable fabric. Insulation layer: using a heat insulation, flame retardant, thermal radiation properties of fabrics. Neck protector: two layer. outer layer is aramid fiber, inner layer is fire-retardant cotton. Comfort layer: comfortable fabric with flame retardant properties. Style: five finger Color: navy blue Applications: suitable for fire protection, the opponent of the wrist, to prevent scratches and cut</p>	<p>7</p>		
<p>LED head flash light</p>		<p>Dimension: 10cm (approximate) Runing time: 4 hr or more Distance 490m or more Output:350 Lumens or more Intensity: 60,000cd or more Any Color</p>	<p>7</p>		
<p>Fire face mask</p>		<p>Item Name: hig+A4:B12h quality double respirator mask/gas mask Model No: CH-M002 Mask material: PVC (polyester optional) Cartridge material: activated carbon Strap: Easily adjustable Style: double active-carbon can or single cartridge optional Size & weight: optional Application: Great for filtering small dusts, mists, metallic fumes, spray paint, chemicals, and small flying particles of LOW toxicit. Standard: CE...</p>	<p>7</p>		