

■ BOX SPECIFICATIONS & FEATURES

External Wall Panel Surface	
Internal Wall Panel Surface	2mm GRP Woven Roving Gelcoat Covered ■
Total Wall Thickness Thickness	2mm GRP Woven Roving Gelcoat Covered III
	104.0 mm
Insulation Material	Extruded Polystyrene XPS
Insulation Density	40 Kg/m ³
Thermal Conductivity	0.025 W/mK
Tensile Strength	600 kPa
Production Method	Vacuum Laminated
Internal Surface Color	RAL 9016
External Surface Color	RAL 9016
Corner Sealant	
Reinforcement	Elastic UV Resistant Polymer
ooring	Available at Side Walls Front Wall Ceiling
Floor Insulation	High Density Extruded XPS 🚍
Substructure	UPN 140 Sandblasted
Main Surface Reinforcement	25mm Marine Plywood
External Surface Cover	0,55 mm Galvanized Steel Sheet
Internal Surface	3 5mm Charlest Alex
Total Thickness	3.5mm Checkered Aluminum 110 mm

	Water Drainage	
Features 8	Accessories Kickplate	Available with PVC Outlet Available Minimum 15
	External Profile Covers Internal Lighting External Lighting	Right April
	Kear Door Side Skirts	Shutter Door with Al
	Internal Wall Rails Tool Box Rear Door Frame	Available on Both Sides Steel Available made from Steel With Rubber Available On Indian
COOLING UNIT	Soor Frame	Available On Internal Walls 1100mm High Available 1 Unit with Lock & Key Made From Stainless Steel
	Bro. / I	

	Made From Stainless Steel
Brand	
Main Running Power Source	
Manning Power Source	Carrier Transicold 💵
	Xaria Xaria
	Vehicle Engi
Evaporator Type Refrigeration C	Xarios 600 Vehicle Engine & Electric Stand-by TM 16
	TM 16
Porator Airfland	Extra Flat My
Condensing Unit Dis	5585 W @ 0° C
Condensing Unit Dimensions Evaporator Dimensions	2000 TO C
Evaporator Dis	2090 m³/Hr
Evaporator Dimensions	155 Kg
Ketrigerand	130/ X 514 v
Power Type	1556 X 614 X 194 mm
Туре	R404 A
	1404 A
	24 VDC
Brand	

TAIL LIFT

		24 VDC	
	Pro 1		
	Brand		_
	Capacity	Anteo II	
	Flattorm T	REP 15/4	
	Material Material	1500	\rightarrow
	Total Denth	TWO FOID Retrain	\rightarrow
	Total Width Platform Extension	Aluminum Extruded	\rightarrow
	Voltage	1583 mm with Extension 2500 mm	
■ Des	Control	Available	
DIMENSIONS			
		24 VDC Stationary & Remote Controlled	\rightarrow
CINO	Verall Height of Box		\dashv

120142	Stationary & po-
A Overall Height of Box	Stationary & Remote Controlled
CILL Serall Height of Roy	aneq.
C Height of Box Flooring	
C1 Clearans	
Daylight p	3790 mm
E I Daylight Door O	1300 mm
E Daylight Door Opening Height H External Height	1190 mm
H External Height of Box	2150 mm
H1 Internal Height of Box	2300 mm
L External Length of Box L1 Internal Length	2600 mm
L1 Internal Length of Box W External Width	2400 mm
W External Width of Box W1 Internal Width	6700 mm
W1 Internal Width of Box	6500 mm
	2600 mm
	2400 mm
	- 190 mm